



by System Sensor

Model Number Cross-Reference

InnovairFlex™ Model	Description	Sensor	Replaces
D2	Conventional 2-wire Photoelectric Duct Smoke Detector with Low-flow Tecnology	2151, Included	DH100LP
D4120	Conventional 4-wire Photoelectric Duct Smoke Detector with Low-flow Technology 24VAC/DC, 120VAC	New 2D51, Included	DH100ACDCLP, DH100ACDCI, DH400ACDCP, DH400ACDCIHT
D4120W	Conventional 4-wire Photoelectric NEMA4 Watertight Rated Duct Smoke Detector with Low-flow Technology 24VAC/DC, 120VAC	New 2D51, Included	DH100ACDCLWP
DNR	Intelligent Non-relay Photoelectric Duct Smoke Detector with Low-flow Technology	No head included, 2251B Sensor head sold separately	DH200PL, DH200RPL
DNRW	Intelligent Non-relay Photoelectric NEMA4 Watertight Rated Duct Smoke Detector with Low-flow Technology	No head included, 2251B Sensor head sold separately	New
D4S	Conventional 4-wire Sensor Component Only with Low-flow Technology	New 2D51, Included	New
D4P120	Conventional 4-wire Power Component Only	NA	New
DST1	1 ft sampling tube	NA	ST-1
DST1.5	1.5 ft sampling tube	NA	ST-1.5
DST3	3 ft sampling tube	NA	ST-3
DST5	5 ft sampling tube	NA	ST-5
DST10	10 ft sampling tube	NA	ST-10
ETX	1 ft steel exhaust tube	NA	A2440-00