



B200S Intelligent Sounder Base

System Sensor B200S series sounder bases set a new standard for performance, installation ease, and aesthetics.



B200S Features

- Addressability for maximum configuration flexibility
- Two volume levels (75 or 85 dBA)
- Multiple event-driven tone outputs
- Supports Continuous, ANSI Temporal 3, ANSI Temporal 4, and March Time tones
- Custom tone capability with some FACP models
- Ability to synchronize with other System Sensor notification devices
- UL 268 and UL 464 compliant
- Pre-wire mounting plate fits various junction box sizes
- Mechanical locking feature prevents removal of attached sensor head
- Additional terminal connections on Canadian model (B200SA) enable silence feature

The B200S sounder base series is designed for new and existing dwelling unit applications. It offers maximum flexibility in installation, configuration, and operation to meet or exceed UL 268 and UL 464 requirements.

The sounder base “listens in” to the communication between the attached sensor head and the fire alarm control panel (FACP) to adopt the same address as the detector, but as a unique device type on the loop. The FACP can then use that address to command an individual sounder — or a group of sounders — to activate. The command set from the panel can be tailored to the specific event, allowing selection of volume, tone, and group. In addition, some FACPs will enable custom tone patterns.[†]

The B200S recognizes the System Sensor synchronization protocol. This enables it to be used as a component of the general evacuation signal — along with other System Sensor horns, horn strobes, and chimes — when connected to a power supply or FACP output capable of generating the System Sensor synchronization pulses.

With its attractive aesthetics, the B200S is ideal for applications where appearance is critical. For example, the sounder base employs a separate mounting plate that installs on various junction box sizes to eliminate unsightly surface-mount boxes. In addition, the mounting plate enables pre-wiring of all connections to speed and simplify installation. The housing then mates with the mounting plate and is locked in position with two retaining screws, which are covered by the installed sensor head for added tamper resistance.

Agency Listings



[†]Refer to the appropriate FACP manual for more information.

Physical Specifications	
Base Diameter	6.875" (17.46 cm)
Base Height	2.0" (5.08 cm) less sensor
Shipping Weight	0.50 lb. (227 gm)
Operating Temperature Range	32°F to 120°F (0°C to 49°C)
Operating Humidity Range	10% to 93% relative humidity (non-condensing)
Electrical Specifications	
External Supply Voltage	16 to 33 VDC (VFWR)
External Supply Standby Current	500 μ A maximum
Alarm Current	35 mA maximum at high-volume setting; 15 mA maximum at low-volume setting
SLC Operating Voltage	15 to 32 VDC
SLC Standby Current	300 μ A maximum
Sound Output	
High Volume	Greater than 85 dBA minimum – measured in a UL reverberant room at 10 ft. 24 Volts (in continuous tone)
Low Volume	Greater than 75 dBA minimum – measured in a UL reverberant room at 10 ft. 24 Volts (in continuous tone)

